

Key Features

- · Built-in Full HD webcam and microphone
- Adjustable vertical angles for greater frame control
- Webcam slide cover ensures total security and privacy
- Ergonomic flexibility with quick release stand
- · Dual front-facing speakers



Product **Description**

The ViewSonic VG2440V is a 24" Full HD video conferencing monitor designed to deliver out-of-the-box video conferencing and high-quality live streaming capabilities. The built-in Full HD webcam allows you to easily adjust the vertical angles to better frame yourself during VC calls and create more engaging content through varied camera angles, while the easy-to-use webcam slide cover ensures total privacy and security when not in use. Providing the full spectrum of ergonomic flexibility, the VG2440V can tilt, swivel, pivot, and height adjust to adapt to any setup or workflow, and the exceptional built-in microphones and dual front-facing speakers ensure you can hear and be heard with absolute clarity and professionalism. Combined with the vDisplay Manager productivity software for efficient multi-tasking and streamlined on-screen display control, the VG2440V is the complete solution for anybody looking for a professional live streaming or video communication experience.



Visit Us www.viewsonic.com

DISPLAY		VIDEO INPUT	-
Display Size (in.):	24	Digital Sync:	TMDS - HDMI (v1.4), PCI-E -
Viewable Area (in.):	23.8	Digital Sylic.	DisplayPort (v1.2)
Panel Type:	IPS Technology	Analog Sync:	Separate/Composite/SOG - RGB Analog
Resolution:	1920 x 1080	ERGONOMICS	-
Resolution Type:	FHD	Height Adjust (mm):	130
Static Contrast Ratio:	1,000:1 (typ)	Swivel:	120°
Dynamic Contrast Ratio:	80M:1	Tilt (Forward/Back):	-5° / 40°
Light Source:	LED	Pivot (Right/Left):	90° / 90°
Brightness:	250 cd/m² (typ)	WEIGHT (IMPERIAL)	
Colours:	16.7M	Net (lbs):	13.3
Colour Space Support:	8 bit (6 bit + Hi-FRC)	Net Without Stand (lbs):	7.9
Aspect Ratio:	16:9	Gross (lbs):	19.2
Response Time (Typical GTG):	5ms	WEIGHT (METRIC)	
Response Time (GTG w/OD):	5ms	Net (kg):	6
Viewing Angles:	178° horizontal, 178° vertical	Net Without Stand (kg):	3.6
Backlight Life (Hours):	30000 Hrs (Min)	Gross (kg):	8.7
Curvature:	Flat	DIMENSIONS (IMPERIAL) (W	
Refresh Rate (Hz):	60	Packaging (in.):	24 x 15.9 x 8.3
Blue Light Filter:	Yes	Physical (in.):	21.6 x 16.02~21.13 x 8.1
Flicker-Free:	Yes	Physical Without Stand (in.): DIMENSIONS (METRIC) (WXF	21.6 x 13.8 x 2
Colour Gamut:	NTSC: 72% size (Typ), sRGB: 104% size (Typ)	Packaging (mm):	609 x 405 x 210
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	Physical (mm):	549 x 406.78~536.78 x 206
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical (mm): Physical Without Stand (mm):	549 x 352 x 50
COMPATIBILITY		GENERAL	040 X 002 X 00
PC Resolution (max):	1920x1080		cTUVus, FCC-B, ICES003, Energy
Mac® Resolution (max):	1920x1080	Demulations	Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy, CE, CE EMC,
PC Operating System:	Windows 7/8/8.1/10 certified; macOS	Regulations:	CB, RoHS, ErP, REACH, WEEE, TCC 8.0, EAC, UkrSEPRO, UKCA, RCM,
PC Operating System.	tested		GEMS, BIS
Mac® Resolution (min): CONNECTOR	1920x1080	PACKAGE CONTENTS:	VG2440V x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB A/B Cable (v3.2;
VGA:	1		Male-Male) x1, Audio Cable (Male- Male) x1, Quick Start Guide x1
USB 3.2 Type A Down Stream:	3		Please dispose of in accordance with
USB 3.2 Type B Up Stream:	1	Recycle/Disposal:	local, state or federal laws.
3.5mm Audio In:	1	Warranty:	*Warranty offered may differ from market to market
3.5mm Audio Out:	1	Power Management:	Energy Star standards, EPEAT
HDMI 1.4:	1	Tower management.	Energy oral crandatus, Er Ern
DisplayPort:	1		
Power in: AUDIO	3-pin Socket (IEC C14 / CEE22)		
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	10.3W		
Eco Mode (optimised):	11.71W		
Consumption (typical):	13.68W		
Consumption (max):	16.52W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	Internal		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Webcam:	2.0M pixel		
Cable Organisation:	Yes		
Microphone: CONTROLS	Yes		
Physical Controls:	Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio/Mic, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing): WALL MOUNT	20% to 90%		
VESA Compatible:	100 x 100 mm		
NPUT SIGNAL	TOU A TOU HIRM		
Frequency Horizontal:	RGB Analog: 16 ~ 83KHz, HDMI (v1.4): 15 ~ 90KHz, DisplayPort		
Frequency Vertical:	(v1.2): 15 ~ 90KHz RGB Analog: 50 ~ 75Hz, HDMI (v1.4): 49 ~ 75Hz, DisplayPort (v1.2):		
Frequency Vertical:	(v1.4): 49 ~ 75Hz, DisplayPort (v1.2): 49 ~ 75Hz Copyright © ViewSonic Corpora		