



48-Port Gigabit Switch

TL-SG1048

■ Overview

The TL-SG1048 Gigabit Ethernet Switch provides you with a high-performance, low-cost, easy-to-use, seamless and standard upgrade to improve old network to 1000Mbps network. All 48 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, the TL-SG1048 can save up to 70% of the power consumption and 80% of the packaging material can be recycled, making it an eco-friendly solution for your business network.

Green Technology

- Saving power 70%
- Recyclable packaging material

High Performance

- IEEE 802.3x flow control
- Non-blocking switching architecture
- 96 Gbps Switching Capacity
- Store and forward
- Auto-MDI/MDIX
- Auto-negotiation
- MAC address auto-learning and auto-aging
- 10KB Jumbo frame

Easy to use

- Plug and Play design



- Details:<http://www.tp-link.com/support/Localesupport.asp>
- German/Austrian/Swiss users are not included



48-Port Gigabit Switch

TL-SG1048


High Performance

All 48 ports are Gigabit RJ-45 ports which can provide large file transferring and also be compatible with 10Mbps and 100Mbps Ethernet devices. Featuring non-blocking switching architecture, TL-SG1048 forwards and filters packets at full wire-speed for maximum throughput. With 10K Jumbo frame, the performance of large files transfers is improved significantly. And IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode alleviate the traffic congestion and make TL-SG1048 work reliably. It's a perfect choice to update your network to Gigabit while protecting your previous investment properly.

Easy to Use

The auto features of this gigabit switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDIX eliminates the need for crossover cables. Auto-negotiation on each port senses the link speed of a network device (10, 100, or 1000 Mbps) and intelligently adjusts for compatibility and optimal performance.

Specifications:

Product Picture	
Model	TL-SG1048
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x
Network Ports	48 * 10/100/1000Mbps RJ45 ports
Auto Negotiation	YES
Auto MDI/MDIX	YES
Systems	Windows 8/7/Vista/XP/2000, Linux/MAC OS
Forwarding Mode	Store and Forward
Switch Capacity	96 Gbps
MAC Address Table	8 K
Jumbo Frame	10 KB
Flow Control	YES
Fanless	NO
Green Technology	NO
Power Saving	Up to 70%
LED	Power, 1000Mbps, Link/Act
Dimensions	17.3 * 10.2 * 1.7 in. (440 * 260 * 44 mm)
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Operating Humidity	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing
Ordering Information	48-Port Gigabit Rackmount Switch

* Maximum power savings when compared to a TP-LINK conventional switch, the real saving rate may vary based on the usage condition.